

tesaflex® 4169 PV8 Floor Marking Tape Premium

tesaflex® 4169 PV8 floor marking tape offers outstanding performance on many high-demanding floor marking applications. tesaflex® 4169 PV8 is a tough plasticized vinyl tape, coated with an aggressive modified rubber-resin adhesive.

Equipped with a very strong and tough vinyl backing, tesaflex® 4169 PV8 features a high resistance to weak chemicals and high abrasions.

The high flexibility of tesaflex® 4169 PV8 allows application in curves without wrinkling.

Its silicon-release coated vinyl backing features a low unwinding force which offers high suitability for use with dispensers.

Technical Data

▪ Backing material	soft PVC	▪ Adhesion to steel	1.6 N/cm
▪ Total thickness	203 µm	▪ Elongation at break	260 %
▪ Type of adhesive	natural rubber	▪ Tensile strength	45 N/cm

Properties

- Suitable for rough surfaces ●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04169>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.