

# **Technical Data Sheet**

## MinuteWeld<sup>™</sup>

### **PRODUCT BRIEF**

Setti Strongth 2300 PSI Set time 1 minute Carves in 1 boar Stie See STRONGER THAN SUPER GLUES Won't Dry Out Bends lestantly MULTI-PURPOSE Tile Most Plastics Ceramic - Flass **RE-SEALABLE** 17212 15 FL. OZ. 125 mL **NO WASTE CAP** 

#### MinuteWeld<sup>™</sup> is a special formulated, high-strength, two-part instant setting epoxy. MinuteWeld<sup>™</sup> will set in one minute under most temperature conditions, fully cures in one hour. MinuteWeld<sup>™</sup> is designed to adhere to multiple surfaces and can be used on ceramic, tile, glass, stone, most plastics, wood and metal. With a strength of 2300 PSI, MinuteWeld<sup>™</sup> sets to a hard, permanent bond.

Part NumberContainer Size50101Carded 25ml Syringe

#### **PRODUCT BENEFITS**

- Dries Clear
- Strength is 2300 PSI
- Won't dry out like super glue
- Sets in 1 minutes
- Cures in 1 hour
- Includes stir stick and mixing tray
- Allows for precise 1 to 1 mix

#### **TYPICAL APPLICATIONS**

- Use on most hard plastics\*, Tile & Ceramic, Wood, PVC, Concrete, Glass, Fiberglass, Stone, Metal and more
- Home, Auto, Toy, Plumbing, Industrial, and Marine Repairs
- Indoor and Outdoor Equipment

#### DIRECTIONS FOR USE

- 1. PREPARE SURFACE: Clear repair area of dirt, grease, oil, paint, rust, etc. For best results use a detergent or degreaser to clean the surface, then roughen surface with file or coarse sandpaper to provide the best repair.
- 2. MIX: After removing the replaceable cap, press down on plunger and squeeze equal amounts onto mixing tray or disposable surface and mix thoroughly.
- 3. APPLICATION: Apply with appropriate tool in an even coat, weld bead or extrude shape as needed.
- 4. DRYING: Sets in 1 minute. Cures in 1 hour. If temperature is below 40°F, then set time is longer.

#### VOC STATUS:

Compliant for sale in all 50 states.

#### DISCLAIMER

\*Not recommended for Polyethylene Plastic (PE), Polypropylene Plastic (PPE), Nylon, and other highly flexible materials and non-porous surfaces.

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use.