



KRUD KUTTER® ADHESIVE REMOVER

DESCRIPTION AND USES

Krud Kutter® Adhesive Remover is a water-based, biodegradable formula that is a safe, effective alternative to hazardous, solvent-based adhesive removers. Removes most glues and adhesives, carpet seam sealer, and mastic. It also removes dirt, grease, grime, heel marks and floor wax. Not recommended for varnished surfaces.

PRODUCT FEATURES

- Water-based
- Biodegradable
- Non-toxic
- Non-flammable

PRODUCTS

SKU	DESCRIPTION
ARJ324	32 oz. Trigger Sprayer
AR014	1 Gallon Bottle
AR05	5 Gallon Pail
AR55	55 Gallon Drum

PRODUCT APPLICATION

DIRECTIONS

Always test on inconspicuous area first. Saturate the adhesive by applying a liberal amount directly onto the finish. Allow time for the remover to work. It will loosen most finishes in 15-30 minutes.

Test scrape a small area to see if finish is ready for removal. Scrape away the softened adhesive with a wide putty knife or scraper. Multiple coats or stubborn finishes may require repeat applications.

For final clean-up, apply onto the surface and wipe clean. Before installing new floor covering, allow surface to dry for 1 hour or more.

CAUTION: EYE AND SKIN IRRITANT. In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention.

KEEP OUT OF REACH OF CHILDREN.

	TECHNICAL DATA	KRK-22
	KRUD KUTTER® ADHESIVE REMOVER	

PHYSICAL PROPERTIES

		ADHESIVE REMOVER
Composition		Proprietary Blend of Biodegradable Surfactants, Detergents and Emulsifiers
Solvents		Water
Weight	Per Gallon	8.42 lbs.
	Per Liter	1.01 kg
Color		Light Yellow
Clarity		Clear Liquid
Odor		Mild
pH (Concentrate)		12-13
VOC (Weight %)		5.0%
Practical Coverage		Varies with type and porosity of surface
Shelf Life		NA
Flash Point		>200°F (93°C)
Caution!		CAUTION: EYE AND SKIN IRRITANT. In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention. KEEP OUT OF REACH OF CHILDREN.
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 877-385-8155
www.rustoleum.com

Form: GDH-541
Rev.:112921